Allround MegaLoop

Defence

The endless rope. The universal Allround MegaLoop sets new standards for round slings used in lifting, towing and securing applications.

New handling standard

High occupational safety thanks to minimal weight and round cross-section.

New versatility standard

Fits all attachment points and can be safely doubled to shorten the effective length and increase load capacity.

New performance standard

Circular-wound Dyneema® high-performance core, highly durable braided cover and precise control of strength and length.

Available in lengths of 2–12 m

Dyneema®

Gleistein

More than Ropes.

Technical data

Elongation at 10% of the breaking load: 0.60 %

7:1 (Europe)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
5	4	10	18	25	10
10	8	20	24	32	20
20	16	40	34	52	25

5:1 (metric tons)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
7	5.6	14	18	25	10
14	11.2	28	24	32	20
28	22.4	56	34	52	25

5:1 (US tons)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
7.7	6.2	15.4	18	25	10
15.4	12.3	30.8	24	32	20
30.6	24.6	61.6	34	52	25