

GeoLink Lashing with PES-Cover

Mooring

Soft shackle in signal yellow colour. Child's play to fasten, holds securely and easy to open again each time.



Safe handling

Injury-free one-person handling



Highest precision

Suitable as sacrificial element due to minimal series variation



Marked pressure points

Enhances safety due to exact positioning

Diameter

20 mm - 32 mm Ø

Technical data

Elongation at 10% of the breaking load: 0.60 %

Elongation at 10% of the breaking load: 0.60 %

R2

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	61.20	546.80
20 mm Ø	80.40	694.10
22 mm Ø	93.60	810.00
24 mm Ø	113.60	983.30
26 mm Ø	124.00	1,073.30
28 mm Ø	152.80	1,299.40
30 mm Ø	173.60	1,426.50
32 mm Ø	186.00	1,471.50

R3

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	91.80	820.10
20 mm Ø	120.60	1,041.20
22 mm Ø	140.40	1,215.00
24 mm Ø	170.40	1,474.90
26 mm Ø	186.00	1,609.90
28 mm Ø	229.20	1,949.10
30 mm Ø	260.40	2,139.80
32 mm Ø	279.00	2,207.30

R4

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	122.40	1,230.20
20 mm Ø	160.80	1,561.80

\emptyset [mm]	Weight [kg/100m]	Bl. real in splice [kN]
22 mm \emptyset	187.20	1,822.50
24 mm \emptyset	227.20	2,212.30
26 mm \emptyset	248.00	2,414.80
28 mm \emptyset	305.60	2,923.60
30 mm \emptyset	347.20	3,209.60
32 mm \emptyset	372.00	3,310.90

Gleistein

More than Ropes.

