

# GeoSquare<sup>®</sup> TailMaster Mooring

Happy end: easy to splice square braid with weight-reducing polyolefin monofilaments that are carefully enveloped in polyester.



## Balanced

High strength, best shock absorption, moderate weight



## Durable

Rugged rope construction, best UV and abrasion resistance



## Best handling

Very flexible, knobby surface, easy to splice

### Diameter

40 mm - 96 mm Ø

### Construction



## Technical data

Elongation at 10% of the breaking load: 1.90 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
40 mm Ø	104.00	369.00	410.00
44 mm Ø	124.00	440.00	489.00
48 mm Ø	148.00	525.00	583.00
52 mm Ø	175.00	615.00	683.00
56 mm Ø	203.00	710.00	789.00
60 mm Ø	230.00	807.00	897.00
64 mm Ø	262.00	908.00	1,009.00
68 mm Ø	299.00	1,030.00	1,144.00
72 mm Ø	331.00	1,140.00	1,267.00
76 mm Ø	369.00	1,270.00	1,411.00
80 mm Ø	411.00	1,397.00	1,552.00
84 mm Ø	460.00	1,545.00	1,717.00
88 mm Ø	502.00	1,690.00	1,878.00
92 mm Ø	550.00	1,850.00	2,056.00
96 mm Ø	593.00	1,984.00	2,204.00

# Gleistein

More than Ropes.

