

PowerPlait Mooring

Lightweight and great value: inexpensive, easy to splice mooring line for inland waterway use.



Always on top

Is buoyant even in fresh water



Distinctive

Striped design for torsion protection and best identifiability



Affordable

Easy to splice square braid at an attractive price

Diameter

16 mm - 96 mm Ø

Construction



Technical data

Elongation at 10% of the breaking load: 1.80 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
16 mm Ø	11.60	42.50	47.20
18 mm Ø	14.70	53.40	59.30
20 mm Ø	18.10	65.50	72.80
22 mm Ø	21.90	78.70	87.40
24 mm Ø	26.10	93.60	104.00
26 mm Ø	30.60	109.00	121.00
28 mm Ø	35.50	125.00	139.00
30 mm Ø	40.80	142.00	158.00
32 mm Ø	46.40	161.00	179.00
36 mm Ø	58.70	202.00	224.00
40 mm Ø	72.50	247.00	274.00
44 mm Ø	87.70	294.00	327.00
48 mm Ø	104.00	347.00	386.00
52 mm Ø	122.00	403.00	448.00
56 mm Ø	142.00	463.00	514.00
60 mm Ø	163.00	525.00	583.00
64 mm Ø	186.00	591.00	657.00
68 mm Ø	210.00	663.00	737.00
72 mm Ø	235.00	738.00	820.00
80 mm Ø	290.00	896.00	996.00
88 mm Ø	351.00	1,070.00	1,189.00
96 mm Ø	417.00	1,260.00	1,400.00

Glestein

More than Ropes.

