

# WinchMaster

Mooring

Everything you could winch for! Economical winch line with exemplary properties.



## Extremely dimensionally stable

Kernmantle construction with compacted XS core



## Extremely light

Buoyant despite polyester component in the Plus cover



## Extremely safe

Robust cover for long-term protection in use under toughest conditions

### Diameter

36 mm - 96 mm Ø

### Construction



## Technical data

Elongation at 10% of the breaking load: 2.80 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
36 mm Ø	74.50	230.00	256.00
40 mm Ø	87.00	280.00	311.00
44 mm Ø	100.00	375.00	417.00
48 mm Ø	129.00	460.00	511.00
52 mm Ø	140.00	520.00	578.00
56 mm Ø	169.00	600.00	667.00
60 mm Ø	192.00	690.00	767.00
64 mm Ø	215.00	800.00	889.00
68 mm Ø	230.00	900.00	1,000.00
72 mm Ø	295.00	1,040.00	1,156.00
84 mm Ø	413.00	1,270.00	1,411.00
96 mm Ø	488.00	1,500.00	1,667.00

# Gleistein

More than Ropes.

