

X-Twin Plus-Cover

Mooring

Exceptional performance, attractively priced: the entry point to the X-Twin class. Buoyant mooring line with extreme strength.



High strenght

Strength-optimised core made of Dyneema® SK78



Quality cover

Affordable, lightweight cover made of a high-quality Plus fibre mix



Perfect handling

Light and flexible for first-class handling under all conditions

Diameter

18 mm - 84 mm Ø

Construction



Technical data

Elongation at 10% of the breaking load: 0.60 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
18 mm Ø	12.80	170.00	189.00
20 mm Ø	19.50	232.00	258.00
22 mm Ø	25.10	303.00	337.00
24 mm Ø	31.00	370.00	411.00
28 mm Ø	39.90	468.00	520.00
32 mm Ø	46.60	543.00	603.00
34 mm Ø	55.00	620.00	689.00
36 mm Ø	63.30	748.00	831.00
38 mm Ø	69.80	815.00	906.00
40 mm Ø	79.50	925.00	1,028.00
42 mm Ø	89.70	1,044.00	1,160.00
44 mm Ø	97.80	1,155.00	1,283.00
48 mm Ø	112.40	1,260.00	1,400.00
50 mm Ø	119.50	1,370.00	1,522.00
52 mm Ø	131.50	1,510.00	1,678.00
54 mm Ø	141.00	1,650.00	1,833.00
56 mm Ø	158.50	1,790.00	1,989.00
62 mm Ø	168.00	1,930.00	2,144.00
64 mm Ø	187.60	2,070.00	2,300.00
68 mm Ø	197.20	2,200.00	2,444.00
70 mm Ø	206.70	2,330.00	2,589.00
72 mm Ø	237.70	2,600.00	2,889.00
74 mm Ø	247.30	2,730.00	3,033.00
76 mm Ø	269.70	2,860.00	3,178.00
78 mm Ø	288.80	3,120.00	3,467.00
80 mm Ø	298.40	3,240.00	3,600.00
82 mm Ø	339.60	3,510.00	3,900.00
84 mm Ø	349.10	3,640.00	4,044.00

Gleistein

More than Ropes.

