

GeoSquare[®] GeoProp Superyacht

No getting it down: Buoyant mooring line, highquality square braid, attractive price.



Simply good

The grippy GeoSquare[®] GeoProp is torsion-free, easy to splice and offers good grip on polished bollards.



Ideal as a towing line

Buoyant, avoids getting caught in the propeller and is easily retrieved from the water.



Value for money

High quality mooring line with good absorption properties at an attractive price.

Diameter

24 mm - 56 mm Ø

Construction



Colors



Technical data

Elongation at 10% of the breaking load: 3.20 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
24 mm Ø	26.00	67.00	74.40
26 mm Ø	30.60	104.00	116.00
28 mm Ø	35.40	119.00	132.00
30 mm Ø	40.70	136.00	151.00
32 mm Ø	46.30	154.00	171.00
36 mm Ø	58.60	191.00	212.00
40 mm Ø	72.30	233.00	259.00
44 mm Ø	87.50	278.00	309.00
48 mm Ø	104.00	327.00	363.00
52 mm Ø	122.00	379.00	421.00
56 mm Ø	142.00	436.00	484.00

Gleistein

More than Ropes.