

# GeoSquare<sup>®</sup> GeoProp Superyacht

No getting it down: Buoyant mooring line, highquality square braid, attractive price.



## Simply good

The grippy GeoSquare<sup>®</sup> GeoProp is torsion-free, easy to splice and offers good grip on polished bollards.



## Ideal as a towing line

Buoyant, avoids getting caught in the propeller and is easily retrieved from the water.



## Value for money

High quality mooring line with good absorption properties at an attractive price.

### Diameter

24 mm - 56 mm Ø

### Construction



### Colors



## Technical data

Elongation at 10% of the breaking load: 3.20 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
24 mm Ø	26.00	67.00	74.40
26 mm Ø	30.60	104.00	116.00
28 mm Ø	35.40	119.00	132.00
30 mm Ø	40.70	136.00	151.00
32 mm Ø	46.30	154.00	171.00
36 mm Ø	58.60	191.00	212.00
40 mm Ø	72.30	233.00	259.00
44 mm Ø	87.50	278.00	309.00
48 mm Ø	104.00	327.00	363.00
52 mm Ø	122.00	379.00	421.00
56 mm Ø	142.00	436.00	484.00

# Gleistein

More than Ropes.