

GeoSquare[®] Polyester Superyacht

Ruggedness squared: Highly abrasion-resistant and durable, perfectly suited as an anchor warp.



Indestructible

Extremely robust and durable, without hardening, best UV resistance.



Simply good

The grippy GeoSquare[®] is torsion-free, easy to splice and offers good grip on polished bollards.



Universal

Excellent mooring line, also suitable as an anchor warp due to its sag line in water.

Diameter

20 mm - 48 mm Ø

Construction



Colors



Technical data

Elongation at 10% of the breaking load: 2.50 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
20 mm Ø	30.30	80.00	88.90
22 mm Ø	36.70	97.00	107.80
24 mm Ø	43.70	110.00	122.00
26 mm Ø	51.20	122.00	136.00
28 mm Ø	59.40	140.00	156.00
30 mm Ø	68.20	159.00	177.00
32 mm Ø	77.60	180.00	200.00
36 mm Ø	98.20	226.00	251.00
40 mm Ø	121.00	275.00	306.00
44 mm Ø	147.00	350.00	389.00
48 mm Ø	175.00	430.00	478.00

Gleistein

More than Ropes.