

GeoLink Lashing towing

Soft shackle in signal yellow colour. Child's play to fasten, holds securely and easy to open again each time.



Safe handling

Injury-free one-person handling



Highest precision

Suitable as sacrificial element due to minimal series variation



Marked pressure points

Enhances safety due to exact positioning

Diameter

18 mm - 32 mm Ø

Construction



Technical data

Elongation at 10% of the breaking load: 0.60 %

Elongation at 10% of the breaking load: 0.60 %

R2

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	61.20	546.80
20 mm Ø	80.40	694.10
22 mm Ø	93.60	810.00
24 mm Ø	113.60	983.30
26 mm Ø	124.00	1,073.30
28 mm Ø	152.80	1,299.40
30 mm Ø	173.60	1,426.50
32 mm Ø	186.00	1,471.50

R3

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	91.80	820.10
20 mm Ø	120.60	1,041.20
22 mm Ø	140.40	1,215.00
24 mm Ø	170.40	1,474.90
26 mm Ø	186.00	1,609.90
28 mm Ø	229.20	1,949.10
30 mm Ø	260.40	2,139.80
32 mm Ø	279.00	2,207.30

R4

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]
18 mm Ø	122.40	1,230.20
20 mm Ø	160.80	1,561.80
22 mm Ø	187.20	1,822.50
24 mm Ø	227.20	2,212.30
26 mm Ø	248.00	2,414.80
28 mm Ø	305.60	2,923.60
30 mm Ø	347.20	3,209.60
32 mm Ø	372.00	3,310.90

Gleistein

More than Ropes.

