

# Texteel<sup>®</sup> One-Four-Four towing

**Big deal: 144 strands meet the highest demands. Long-lasting, high-performance rope with large diameter**



## Strength

12 heat-set braids made from Texteel<sup>®</sup> are unified to form a high-performance rope with huge diameter



## Spliceability

Coverless construction with compact sub-braids enables unbeatably short splicing times



## Durability

Excellent abrasion resistance even without a protective cover – thanks to the special strand construction and highly effective coating

### Diameter

40 mm - 104 mm Ø

## Technical data

Elongation at 10% of the breaking load: 0.40 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
40 mm Ø	92.20	1,085.70	1,206.00
44 mm Ø	107.60	1,341.20	1,490.00
48 mm Ø	147.60	1,703.10	1,892.00
52 mm Ø	172.20	1,979.00	2,199.00
56 mm Ø	215.20	2,458.90	2,732.00
60 mm Ø	221.40	2,518.90	2,799.00
64 mm Ø	245.90	2,781.80	3,091.00
68 mm Ø	270.50	3,047.40	3,386.00
72 mm Ø	319.70	3,579.40	3,977.00
76 mm Ø	344.50	3,841.00	4,268.00
80 mm Ø	369.30	4,092.10	4,547.00
84 mm Ø	461.20	5,088.10	5,653.00
88 mm Ø	491.90	5,393.20	5,992.00
92 mm Ø	507.30	5,538.30	6,154.00
96 mm Ø	574.90	6,237.00	6,930.00
100 mm Ø	608.70	6,575.70	7,306.00
104 mm Ø	642.50	6,896.60	7,663.00

# Gleistein

More than Ropes.