

X-Twin Dyneema[®] SSC-Cover towing

Lasts almost forever (unfortunately): Compact yet flexible, buoyant high-performance towline with unbeatably resistant SSC sheath.



Core

Strength-optimised core made of Dyneema[®] SK78



Abrasion resistance

Exceptionally abrasion-resistant SSC cover made of sub-braids with Dyneema[®].



Handling

Lightweight and flexible for first-class handling under all conditions

Diameter

46 mm - 80 mm Ø

Construction



Technical data

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
46 mm Ø	132.90	1,370.00	1,522.00
48 mm Ø	143.80	1,510.00	1,678.00
50 mm Ø	154.60	1,650.00	1,833.00
52 mm Ø	169.10	1,790.00	1,989.00
56 mm Ø	186.60	1,930.00	2,144.00
62 mm Ø	224.10	2,070.00	2,300.00
64 mm Ø	240.50	2,200.00	2,444.00
66 mm Ø	258.10	2,330.00	2,589.00
68 mm Ø	287.10	2,600.00	2,889.00
70 mm Ø	299.40	2,730.00	3,033.00
72 mm Ø	311.70	2,860.00	3,178.00
74 mm Ø	333.50	3,120.00	3,467.00
76 mm Ø	345.80	3,240.00	3,600.00
78 mm Ø	367.60	3,510.00	3,900.00
80 mm Ø	379.90	3,640.00	4,044.00

Gleistein

More than Ropes.

