

X-Twin HS Dyneema® -Cover towing

100%: pure Dyneema®, buoyant towing line delivering extreme strength, lowest elongation with a slender yet abrasion-resistant cover



Ultimate strength

Core made with heat-set Dyneema® SK78



Abrasion resistance

Very abrasion-resistant, light cover made with Dyneema®



Perfect handling

Extremely light and compact ensuring exemplary handling

Diameter

22 mm - 68 mm Ø

Technical data

Elongation at 10% of the breaking load: 0.30 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
22 mm Ø	32.60	482.00	536.00
24 mm Ø	38.80	559.00	621.00
28 mm Ø	44.20	639.00	710.00
32 mm Ø	54.30	770.00	856.00
34 mm Ø	60.30	839.00	932.00
36 mm Ø	67.60	953.00	1,059.00
38 mm Ø	77.60	1,075.00	1,194.00
40 mm Ø	87.30	1,190.00	1,322.00
42 mm Ø	98.60	1,298.00	1,442.00
44 mm Ø	105.10	1,411.00	1,568.00
46 mm Ø	122.80	1,700.00	1,889.00
48 mm Ø	144.60	1,988.00	2,209.00
50 mm Ø	157.80	2,132.00	2,369.00
52 mm Ø	172.40	2,266.00	2,518.00
54 mm Ø	185.60	2,400.00	2,667.00
56 mm Ø	209.50	2,678.00	2,976.00
60 mm Ø	222.70	2,812.00	3,124.00
62 mm Ø	231.80	2,946.00	3,273.00
64 mm Ø	249.70	3,214.00	3,571.00
68 mm Ø	274.00	3,337.00	3,708.00

Gleistein

More than Ropes.

