

# X-Twin HS Dyneema<sup>®</sup> SSC-Cover

Towing

**With full force: extremely compact and buoyant high-performance towing line with lowest elongation and the unsurpassed durability of the SSC cover**



## Ultimate strength

Core made of heat-set Dyneema<sup>®</sup> SK78



## Abrasion resistant

Exceptionally abrasion-resistant SSC cover from sub-braids made with Dyneema<sup>®</sup>



## Handling

Extremely light and compact ensuring exemplary handling

### Diameter

40 mm Ø - 68 mm Ø

### Construction



## Technical data

| Ø [mm]  | Weight [kg/100 m] | Bl. real in splice [kN] | Bl. linear DIN according to EN ISO 2307 [kN] |
|---------|-------------------|-------------------------|--|
| 40 mm Ø | 104.90            | 1,298.00                | 1,442.22                                     |
| 42 mm Ø | 123.50            | 1,411.00                | 1,567.78                                     |
| 44 mm Ø | 142.30            | 1,700.00                | 1,888.89                                     |
| 46 mm Ø | 161.20            | 1,988.00                | 2,208.89                                     |
| 48 mm Ø | 171.30            | 2,132.00                | 2,368.89                                     |
| 50 mm Ø | 182.80            | 2,266.00                | 2,517.78                                     |
| 52 mm Ø | 196.60            | 2,400.00                | 2,666.67                                     |
| 56 mm Ø | 224.10            | 2,678.00                | 2,975.56                                     |
| 62 mm Ø | 260.90            | 2,812.00                | 3,124.44                                     |
| 64 mm Ø | 276.70            | 2,946.00                | 3,273.33                                     |
| 66 mm Ø | 302.80            | 3,214.00                | 3,571.11                                     |
| 68 mm Ø | 323.90            | 3,337.00                | 3,707.78                                     |

# Gleistein

More than Ropes.

