

GeoTwist[®] Polyester

Watersports Cruising

Extremely durable, flexible and economic mooring line



Indestructible

Extremely robust and durable, without hardening, best UV resistance.



Quality pays dividends

Carefully constructed, high quality line at a low price.



Universal

Excellent mooring line, also suitable as anchor warp due to its sag line in water.

Diameter

8 mm - 24 mm Ø

Construction



Colors



Technical data

Elongation at 10% of the breaking load: 4.00 %

| Ø [mm] | Weight [kg/100 m] | Bl. real in splice [kN] | Bl. linear DIN according to EN ISO 2307 [kN] |
|-----------|----------------------|-------------------------------|--|
| 8 mm Ø | 4.85 | 11.50 | 12.80 |
| 10 mm Ø | 7.58 | 18.50 | 20.60 |
| 12 mm Ø | 10.90 | 30.00 | 33.30 |
| 14 mm Ø | 14.90 | 39.00 | 43.30 |
| 16 mm Ø | 19.40 | 50.00 | 55.60 |
| 18 mm Ø | 24.60 | 64.00 | 71.10 |
| 20 mm Ø | 30.30 | 84.00 | 93.30 |
| 22 mm Ø | 36.70 | 98.00 | 108.90 |
| 24 mm Ø | 43.70 | 115.00 | 128.00 |

Gleistein

More than Ropes.