GeoTwist® Thempest watersports Cruising

The benchmark for traditional vessels: Resilient twisted rope in a hemp or bronze tone.



Indestructible

Extremely robust and durable with high strength, best weather and UV resistance.



Traditional look

Three-strand laid construction made of a technically superior fibre mix in two elegant natural shades.



Does it all

Universal suitability for everything from a static guy or running rigging to mooring lines.

Diameter 6 mm - 36 mm Ø Construction

Colors



Technical data

Elongation at 10% of the breaking load: 3.20 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	BI. linear DIN according to EN ISO 2307 [kN]
6 mm Ø	2.40	6.50	7.20
8 mm Ø	3.70	11.00	12.20
10 mm Ø	5.30	16.50	18.30
12 mm Ø	8.40	24.00	26.70
14 mm Ø	10.60	31.00	34.40
16 mm Ø	14.10	41.00	45.60
18 mm Ø	18.30	51.00	56.70
20 mm Ø	22.60	62.50	69.40
22 mm Ø	27.30	76.00	84.40
24 mm Ø	32.50	87.00	96.70
26 mm Ø	38.20	102.50	114.00
28 mm Ø	44.30	120.00	133.00
30 mm Ø	50.80	135.00	150.00
32 mm Ø	57.80	155.00	172.00
36 mm Ø	73.20	195.00	217.00



More than Ropes.